

FIS Gate Gard™

Gate Gard™

The FIS Gate Gard™ mechanism protects gateways and other openings from unauthorized access. It uses the existing 9/125µm fiber within the Fiber Fence® system, so no additional power is required.

The FIS Gate Gard™ includes an arm/disarm feature that allows only authorized personnel to enter or exit without triggering an alarm.

The FIS Gate Gard™ contains standard deadbolts and a keyed reset for convenience which allows users to reset the plunger within the unit without having to physically open the device after an alarm has been triggered.

FIS Gate Gards™ are used with our Fiber Fence 3000, Fiber Fence 50 and Fiber Fence Din Rail units.



FEATURES

- Low cost
- No power supply required
- Compact and lightweight
- Multiple mounting configurations
- Quick Re-settable with keyed lock

INSTRUMENT SPECIFICATIONS

| | |
|--------------------------------|--------------------------------|
| Material..... | ABS Grade Delrin machined PVC |
| Operating Temperature..... | -20°C to 60°C (-68°F to 140°F) |
| Power Supply Requirements..... | None |
| Dimensions..... | 5 3/4"H x 7 3/4"W x 1.78"D |
| Weight..... | 2.5 Lbs |
| Fiber Type..... | 9/125µm |
| Mounting Options..... | Gate openings and closures |



1 800 5000 FIS
1 800 5000 347

161 Clear Road • Oriskany, NY 13424
TEL 315-736-2206 • FAX 315-736-2285
E-Mail Info@fiberinstrumentsales.com
Website www.fiberinstrumentsales.com
www.fiber-fence.com