

# FIS Mouse Trip®

Mouse Trip®

FIS Mouse Trips® are designed to be mounted to the fence line. When tripped, an internal plunger creates a loss of light which is recognized by the control unit and activates alarm mode. They have been designed for dependable performance during the extended deployment in harsh weather environments. It is water resistant, dust proof, UV protected and able to stand up to the extremes in temperature fluctuations. The Mouse Trip® requires minimal maintenance throughout its service life. Once installed, the Mouse Trip® will provide years of reliable protection.

FIS also offers a second version Mouse Trip® with a quick re-set feature. This feature allows the Mouse Trip® to be reset with the help of a special tool, without having to open the entire unit.

FIS Mouse Trips® are loaded with 9/125µm sensing fiber and are used with our Fiber Fence 3000, Fiber Fence 50 and Fiber Fence Din Rail units.



## FEATURES

- Low Cost
- UV protected
- No power supply required
- Compact and lightweight
- Multiple mounting configurations
- Quick Re-settable Version also available

## INSTRUMENT SPECIFICATIONS

|                                |                                |
|--------------------------------|--------------------------------|
| Material.....                  | UV protected ABS               |
| Operating Temperature.....     | -20°C to 60°C (-68°F to 140°F) |
| Power Supply Requirements..... | None                           |
| Dimensions.....                | 9.75"L x 3.1W x 6.00" H        |
| Fiber Type.....                | 9/125µm                        |
| Mounting Options.....          | Pole, wall (concrete or brick) |

\*All specifications tested with 9/125µm fiber



1 800 5000 FIS  
1 800 5000 347

161 Clear Road • Oriskany, NY 13424  
TEL 315-736-2206 • FAX 315-736-2285  
E-Mail [Info@fiberinstrumentsales.com](mailto:Info@fiberinstrumentsales.com)  
Website [www.fiberinstrumentsales.com](http://www.fiberinstrumentsales.com)  
[www.fiber-fence.com](http://www.fiber-fence.com)

REV. B 03/14/07